1995 *FPJ* SUBJECT AND AUTHOR INDEX

All of the articles in the 1995 *Forest Products Journal*, volume 45, are listed both by subject and by author. The Subject Index is organized according to the Forest Products Society Division and Technical Interest Group structure. The Author Index lists senior author entries that give complete information for the article, and coauthor entries that refer back to the senior author. Reprints of most articles are available at $6 each. Bulk rates are also available. Please give reprint numbers when ordering. When printer-quality reprints are no longer available, photocopies can be ordered at 50 cents per page. All orders are subject to a $6 minimum charge plus 15 percent shipping and handling, 20 percent in other countries. There is a charge of $6 for a copy of the 1995 *FPJ* Subject and Author Index.

MANAGEMENT

ECONOMICS & FINANCIAL MANAGEMENT

Comparing the Capital Asset Pricing Model and Capital Budgeting Techniques to Analyze Timber Investments, J.E. Wagner, F.W. Cubbage, and C.H. Redmond, 7/8:69-77 (No. 8121).

Perspectives on the Changing Economic Structure of the North American Softwood Lumber Industry, L.C. Irland, 6:53-60 (No. 8230).

Producing Hardwood Dimension Parts Directly From Logs: An Economic Feasibility Study, W. Lin, D.E. Kline, P.A. Araman, and J.K. Wiedenbeck, 6:38-46 (No. 8248).

Productivity Characteristics of the U.S. Wood Cabinet Industry, J.W. Punches, E.N. Hansen, and R.J. Bush, 10:33-38 (No. 8253).

Regional Differences in the Eastern Hardwood Sawmilling Industry, W.G. Luppold, 10:39-43 (No. 8263).

Systems Approach to Equipment Replacement in Wood Products Manufacturing, H.F. Carino, W. Lin, K. Muehlenfeld, and Y. Li, 6:61-68 (No. 8245).

Wood Products Mill Improvement: An Important Component of Rural Development, H.F. Carino, W. Lin, K. Muehlenfeld, J. Gober, and P. Waldrop, 6:47-52 (No. 8234).

MARKETING

An Analysis of Tropical Hardwood Product Importation and Consumption in the United States, P.M. Smith, M.P. Haas, and W.G. Luppold, 4:31-38 (No. 8165).

The Effect of Retail Promotions on Homecenter Shopping Behavior, F.J. Mulhern and J.H. Michael, 3:31-36 (No. 8172).

Estimating the Tropical/Temperate Mix of European Hardwood Lumber Imports, B.G. Hansen, 1:37-39 (No. 8116).

Forest Resources and Wood Properties of Commerical Tree Species in the Russian Far East, O. Krankina and R.L. Ethington, 10:44-50 (No. 8247).

Information Sources Used by Furniture Retailers: The Importance of Furniture Markets, J.H. Michael and P.M. Smith, 4:25-30 (No. 8221).

A Marketing Strategy Comparison: Finland, Western United States, and British Columbia, J.S. Niemela and P.M. Smith, 11/12:27-35 (No. 8286).

Profile of the California Furniture Industry: Structure, Product Types, and Wood Use, D.H. Cohen and D. Goudie, 6:31-37 (No. 8216).

UPC Barcoding for Homecenter Retail Customers: The Wood Products Supplier Perspective, R.P. Vlosky and P.M. Smith, 2:35-40 (No. 8198).

Use of Wood Raw Materials by the U.S. Millwork Industry in 1990, D. Briggs and L. Bialozynski, 2:27-34 (No. 8158).

Visual Impressions of Features in Scots Pine Wood Surfaces: A Qualitative Study, N.O. Broman, 3:61-66 (No. 8146).

PRODUCTION MANAGEMENT

Systems Approach to Equipment Replacement in Wood Products Manufacturing, H.F. Carino, W. Lin, K. Muehlenfeld, and Y. Li, 6:61-68 (No. 8245).

RESEARCH MANAGEMENT

Directions for Duration-of-Load Research, D.V. Rosowsky and K.J. Fridley, 3:85-88 (No. 8193).

PROCESSES

DRYING & STORAGE

Applied Drying Technology, 1988 to 1993, M.R. Milota and E.M. Wengert, 5:33-42 (No. 8285).

Controlling Corrosion in Lumber Dry Kiln Buildings, R.L. Little and W.W. Moschler, 5:55-58 (No. 8258).

The Correlation Between Green Density and the Occurrence of Honeycomb in Kiln-Dried Red Oak Lumber, R.A. Harris and P.A. Araman, 5:53-54 (No. 7940).

Drying 40-mm-Thick Slash Pine in 2.5 Hours at 200°C, A.M. McNaught and D.K. Gough, 1:51-54 (No. 7965).

Effects of Long-Term Storage of Southern Pine Sawlogs Under Water Sprinklers, J.H. Syme and J.R. Saucier, 1:47-50 (No. 8186).

Flattening Wavy Eucalyptus Veneer Through Pressure and Temperature: A Preliminary Laboratory Study, H.P. Steinhagen, V.F. Sagner, R.A. Ananias, and M.J. Poblete, 11/12:71-73 (No. 8187).

Green Dimensioning: A Review of Processing, Handling, Drying, and Marketing, J.S. Gephart, H.D. Petersen, and S.M. Bratkovich, 5:69-73 (No. 8257).

How to Achieve Effective Wet Storage of Pine Logs (*Pinus sylvestris*) With a Minimum Amount of Water, T. Elowsson and K. Liukko, 11/12:36-42 (No. 8246).

Investigation of Potential Toxicity and Mutagenicity of Distillates From the Drying of Five Species of Wood, J.T. Singer, J.A. Jackson, and R.W. Rice, 5:45-50 (No. 8238).

Nondestructive Evaluation of Green Defect-Prone Red Oak Lumber: A Pilot Study, R.J. Ross, J.J. Fuller, and J.R. Dramm, 11/12:51-52 (No. 8316).

Nondestructive Evaluation of Honeycomb and Surface Checks in Red Oak Lumber, J.J. Fuller, R.J. Ross, and J.R. Dramm, 5:42-44 (No. 8324).

Shrinkage and Set in Drying of 4 by 4 Douglas-fir Lumber, Q. Wu and M.R. Milota, 5:59-63 (No. 8182).

Transport Coefficients for Six Log and Lumber End Coatings, R.W. Rice, 5:64-68 (No. 8188).

Variation of Final Moisture Content of 4/4 Yellow-Poplar Lumber Dried in a Small Dehumidification Kiln, J.P. Armstrong and D.W. Patterson, 5:51-52 (No. 8290).

ENERGY GENERATION & CONSERVATION

Higher Heating Values for Pellets Made From Woodwaste and Recycled Newsprint, R.W. Rice and R.M. Willey, 1:84-85 (No. 8179).

1995 *FPJ* SUBJECT AND AUTHOR INDEX

All of the articles in the 1995 *Forest Products Journal*, volume 45, are listed both by subject and by author. The Subject Index is organized according to the Forest Products Society Division and Technical Interest Group structure. The Author Index lists senior author entries that give complete information for the article, and coauthor entries that refer back to the senior author. Reprints of most articles are available at $6 each. Bulk rates are also available. Please give reprint numbers when ordering. When printer-quality reprints are no longer available, photocopies can be ordered at 50 cents per page. All orders are subject to a $6 minimum charge plus 15 percent shipping and handling, 20 percent in other countries. There is a charge of $6 for a copy of the 1995 *FPJ* Subject and Author Index.

MANAGEMENT

ECONOMICS & FINANCIAL MANAGEMENT

Comparing the Capital Asset Pricing Model and Capital Budgeting Techniques to Analyze Timber Investments, J.E. Wagner, F.W. Cubbage, and C.H. Redmond, 7/8:69-77 (No. 8121).

Perspectives on the Changing Economic Structure of the North American Softwood Lumber Industry, L.C. Irland, 6:53-60 (No. 8230).

Producing Hardwood Dimension Parts Directly From Logs: An Economic Feasibility Study, W. Lin, D.E. Kline, P.A. Araman, and J.K. Wiedenbeck, 6:38-46 (No. 8248).

Productivity Characteristics of the U.S. Wood Cabinet Industry, J.W. Punches, E.N. Hansen, and R.J. Bush, 10:33-38 (No. 8253).

Regional Differences in the Eastern Hardwood Sawmilling Industry, W.G. Luppold, 10:39-43 (No. 8263).

Systems Approach to Equipment Replacement in Wood Products Manufacturing, H.F. Carino, W. Lin, K. Muehlenfeld, and Y. Li, 6:61-68 (No. 8245).

Wood Products Mill Improvement: An Important Component of Rural Development, H.F. Carino, W. Lin, K. Muehlenfeld, J. Gober, and P. Waldrop, 6:47-52 (No. 8234).

MARKETING

An Analysis of Tropical Hardwood Product Importation and Consumption in the United States, P.M. Smith, M.P. Haas, and W.G. Luppold, 4:31-38 (No. 8165).

The Effect of Retail Promotions on Homecenter Shopping Behavior, F.J. Mulhern and J.H. Michael, 3:31-36 (No. 8172).

Estimating the Tropical/Temperate Mix of European Hardwood Lumber Imports, B.G. Hansen, 1:37-39 (No. 8116).

Forest Resources and Wood Properties of Commerical Tree Species in the Russian Far East, O. Krankina and R.L. Ethington, 10:44-50 (No. 8247).

Information Sources Used by Furniture Retailers: The Importance of Furniture Markets, J.H. Michael and P.M. Smith, 4:25-30 (No. 8221).

A Marketing Strategy Comparison: Finland, Western United States, and British Columbia, J.S. Niemela and P.M. Smith, 11/12:27-35 (No. 8286).

Profile of the California Furniture Industry: Structure, Product Types, and Wood Use, D.H. Cohen and D. Goudie, 6:31-37 (No. 8216).

UPC Barcoding for Homecenter Retail Customers: The Wood Products Supplier Perspective, R.P. Vlosky and P.M. Smith, 2:35-40 (No. 8198).

Use of Wood Raw Materials by the U.S. Millwork Industry in 1990, D. Briggs and L. Bialozynski, 2:27-34 (No. 8158).

Visual Impressions of Features in Scots Pine Wood Surfaces: A Qualitative Study, N.O. Broman, 3:61-66 (No. 8146).

PRODUCTION MANAGEMENT

Systems Approach to Equipment Replacement in Wood Products Manufacturing, H.F. Carino, W. Lin, K. Muehlenfeld, and Y. Li, 6:61-68 (No. 8245).

RESEARCH MANAGEMENT

Directions for Duration-of-Load Research, D.V. Rosowsky and K.J. Fridley, 3:85-88 (No. 8193).

PROCESSES

DRYING & STORAGE

Applied Drying Technology, 1988 to 1993, M.R. Milota and E.M. Wengert, 5:33-42 (No. 8285).

Controlling Corrosion in Lumber Dry Kiln Buildings, R.L. Little and W.W. Moschler, 5:55-58 (No. 8258).

The Correlation Between Green Density and the Occurrence of Honeycomb in Kiln-Dried Red Oak Lumber, R.A. Harris and P.A. Araman, 5:53-54 (No. 7940).

Drying 40-mm-Thick Slash Pine in 2.5 Hours at 200°C, A.M. McNaught and D.K. Gough, 1:51-54 (No. 7965).

Effects of Long-Term Storage of Southern Pine Sawlogs Under Water Sprinklers, J.H. Syme and J.R. Saucier, 1:47-50 (No. 8186).

Flattening Wavy Eucalyptus Veneer Through Pressure and Temperature: A Preliminary Laboratory Study, H.P. Steinhagen, V.F. Sagner, R.A. Ananias, and M.J. Poblete, 11/12:71-73 (No. 8187).

Green Dimensioning: A Review of Processing, Handling, Drying, and Marketing, J.S. Gephart, H.D. Petersen, and S.M. Bratkovich, 5:69-73 (No. 8257).

How to Achieve Effective Wet Storage of Pine Logs (*Pinus sylvestris*) With a Minimum Amount of Water, T. Elowsson and K. Liukko, 11/12:36-42 (No. 8246).

Investigation of Potential Toxicity and Mutagenicity of Distillates From the Drying of Five Species of Wood, J.T. Singer, J.A. Jackson, and R.W. Rice, 5:45-50 (No. 8238).

Nondestructive Evaluation of Green Defect-Prone Red Oak Lumber: A Pilot Study, R.J. Ross, J.J. Fuller, and J.R. Dramm, 11/12:51-52 (No. 8316).

Nondestructive Evaluation of Honeycomb and Surface Checks in Red Oak Lumber, J.J. Fuller, R.J. Ross, and J.R. Dramm, 5:42-44 (No. 8324).

Shrinkage and Set in Drying of 4 by 4 Douglas-fir Lumber, Q. Wu and M.R. Milota, 5:59-63 (No. 8182).

Transport Coefficients for Six Log and Lumber End Coatings, R.W. Rice, 5:64-68 (No. 8188).

Variation of Final Moisture Content of 4/4 Yellow-Poplar Lumber Dried in a Small Dehumidification Kiln, J.P. Armstrong and D.W. Patterson, 5:51-52 (No. 8290).

ENERGY GENERATION & CONSERVATION

Higher Heating Values for Pellets Made From Woodwaste and Recycled Newsprint, R.W. Rice and R.M. Willey, 1:84-85 (No. 8179).

FINISHING & OVERLAYING

The Effect of Surface Roughness on the Performance of Finishes. Part 1. Roughness Characterization and Stain Performance, K. Richter, W.C. Feist, and M.T. Knaebe, 7/8:91-97 (No. 8254).

Parameters Affecting the Surface Finish of Planed Sitka Spruce, D.J. Lavery, D. McLarnon, J.M. Taylor, S. Moloney, and A. Atanackovic, 4:45-50 (No. 8201).

Performance and Durability of Finishes on Previously Coated CCA-Treated Wood, W.C. Feist and A.S. Ross, 9:29-36 (No. 8227).

MILLING & MACHINING

Design and Evaluation of Log-to-Dimension Manufacturing Systems Using System Simulation, W. Lin, D.E. Kline, P.A. Araman, and J.K. Wiedenbeck, 3:37-44 (No. 8217).

Effect of Knife Clamp, Log Diameter, and Species on the Size Distribution of Pulp Chips Produced by a Chipper-Canter, R.E. Hernández and B. Quirion, 7/8:83-90 (No. 8184).

The Effect of Log Length and Lumber Thickness Over-Allowance on Lumber Recovery, D.Z. Zavala, 2:41-45 (No. 8140).

The Influence of Sawkerf and Target Size Reductions on Sawmill Revenue and Volume Recovery, T.C. Maness and Y. Lin, 11/12:43-50 (No. 8222).

Parameters Affecting the Surface Finish of Planed Sitka Spruce, D.J. Lavery, D. McLarnon, J.M. Taylor, S. Moloney, and A. Atanackovic, 4:45-50 (No. 8201).

A Procedure for Determining the Benefits of Sorting Lumber By Grade Prior to Rough Mill Processing, P.H. Steele and R. Gazo, 6:69-73 (No. 8191).

Rough Mill Analysis Model, R. Gazo and P.H. Steele, 4:51-53 (No. 8189).

Rough Mill Simulations Reveal That Productivity When Processing Short Lumber Can Be High, J.K. Wiedenbeck and P.A. Araman, 1:40-46 (No. 8185).

Simplified Bandsaw Tensioning Procedure to Improve Blade Stiffness and Cutting Accuracy, J. Taylor and S.G. Hutton, 4:38-44 (No. 8117).

Understanding That Red Oak Lumber Has a Better and Worse End, C.J. Gatchell, J.K. Wiedenbeck, and E.S. Walker, 4:54-60 (No. 8229).

TIMBER PRODUCTION & HARVESTING

Comparing the Capital Asset Pricing Model and Capital Budgeting Techniques to Analyze Timber Investments, J.E. Wagner, F.W. Cubbage, and C.H. Redmond, 7/8:69-77 (No. 8121).

Comparison of Two Thinning Systems. Part 1. Stand and Site Impacts, B.L. Lanford and B.J. Stokes, 5:74-79 (No. 8228).

Costs Associated with Harvest Activities for Major Harvest Systems in Montana, C.E. Keegan, III, C.E. Fiedler, and D.P. Wichman, 7/8:78-82 (No. 8242).

Maine Stumpage Prices: Characteristics and Trends from 1963 to 1990, T.E. Howard and W.E. Chase, 1:31-36 (No. 8123).

SOLID WOOD PRODUCTS

HARDWOOD LUMBER

An Analysis of Tropical Hardwood Product Importation and Consumption in the United States, P.M. Smith, M.P. Haas, and W.G. Luppold, 4:31-38 (No. 8165).

Bulk Density of Bottomland Hardwoods in East Texas and West Louisiana, J.D. Lenhart, J.T. Lee, and H.A. Londo, 10:85-88 (No. 8096).

The Correlation Between Green Density and the Occurrence of Honeycomb in Kiln-Dried Red Oak Lumber, R.A. Harris and P.A. Araman, 5:53-54 (No. 7940).

Design and Evaluation of Log-to-Dimension Manufacturing Systems Using System Simulation, W. Lin, D.E. Kline, P.A. Araman, and J.K. Wiedenbeck, 3:37-44 (No. 8217).

Differences in Moisture Content and Shrinkage Between Innerwood and Outerwood of a Single Cottonwood Tree, T.F. Shupe, E.T. Choong, and M.D. Gibson, 10:89-92 (No. 8294).

Differences in Moisture Content and Shrinkage Between Outerwood, Middlewood, and Corewood of Two Yellow-Poplar Trees, T.F. Shupe, E.T. Choong, and M.D. Gibson, 9:85-90 (No. 8256).

Estimating the Tropical/Temperate Mix of European Hardwood Lumber Imports, B.G. Hansen, 1:37-39 (No. 8116).

Forest Resources and Wood Properties of Commerical Tree Species in the Russian Far East, O. Krankina and R.L. Ethington, 10:44-50 (No. 8247).

Green Dimensioning: A Review of Processing, Handling, Drying, and Marketing, J.S. Gephart, H.D. Petersen, and S.M. Bratkovich, 5:69-73 (No. 8257).

Improving Visual Color Sorting of Dimension Stock, A.D. Pugel, J.E. Phelps, and D.D. Stokke, 11/12:57-60 (No. 8267).

Investigation for Brittleheart in Two *Eucalyptus Regnans* Logs, J.L. Yang and E.F. Dougal, 11/12:93-97 (No. 8277).

Nondestructive Evaluation of Green Defect-Prone Red Oak Lumber: A Pilot Study, R.J. Ross, J.J. Fuller, and J.R. Dramm, 11/12:51-52 (No. 8316).

Nondestructive Evaluation of Honeycomb and Surface Checks in Red Oak Lumber, J.J. Fuller, R.J. Ross, and J.R. Dramm, 5:42-44 (No. 8324).

A Procedure for Determining the Benefits of Sorting Lumber By Grade Prior to Rough Mill Processing, P.H. Steele and R. Gazo, 6:69-73 (No. 8191).

Producing Hardwood Dimension Parts Directly From Logs: An Economic Feasibility Study, W. Lin, D.E. Kline, P.A. Araman, and J.K. Wiedenbeck, 6:38-46 (No. 8248).

Regional Differences in the Eastern Hardwood Sawmilling Industry, W.G. Luppold, 10:39-43 (No. 8263).

Rough Mill Analysis Model, R. Gazo and P.H. Steele, 4:51-53 (No. 8189).

Rough Mill Simulations Reveal That Productivity When Processing Short Lumber Can Be High, J.K. Wiedenbeck and P.A. Araman, 1:40-46 (No. 8185).

Quality Characteristics of Appalachian Red Oak Lumber, J.K. Wiedenbeck, C.J. Gatchell, and E.S. Walker, 3:45-50 (No. 8200).

Understanding That Red Oak Lumber Has a Better and Worse End, C.J. Gatchell, J.K. Wiedenbeck, and E.S. Walker, 4:54-60 (No. 8229).

Variation in Lightness of White Oak Dimension Stock, D.D. Stokke, A.D. Pugel, and J.E. Phelps, 10:51-56 (No. 8199).

Wood Dust Concentrations for Three Hardwood Species and Moisture Contents, C.A. Lefevre, C.C. Hassler, and W.R. Myers, 2:53-58 (No. 8161).

Wood Products Mill Improvement: An Important Component of Rural Development, H.F. Carino, W. Lin, K. Muehlenfeld, J. Gober, and P. Waldrop, 6:47-52 (No. 8234).

SOFTWOOD LUMBER

Bending Strength of Spruce End-Grain Butt-Joints Using Resorcinol Formaldehyde-Based Adhesives, J-E. P. Nordström, 6:77-83 (No. 8210).

Decay and Soil Depletion Studies With Polymer/Boron Preservative Systems, R.J. Murphy, H.M. Barnes, and S.M. Gray, 9:77-81 (No. 8270).

Durability of Dahurian Larch, J.J. Morrell and C.M. Freitag, 1:77-78 (No. 8170).

The Effect of Log Length and Lumber Thickness Over-Allowance on Lumber Recovery, D.Z. Zavala, 2:41-45 (No. 8140).

Effect of Wood Moisture Content on Diffusion of Boron-Based Biocides Through Douglas-fir and Western Hemlock Lumber, J.J. Morrell and C.M. Freitag, 3:51-55 (No. 8213).

Effects of Long-Term Storage of Southern Pine Sawlogs Under Water Sprinklers, J.H. Syme and J.R. Saucier, 1:47-50 (No. 8186).

Effects of Redrying Schedule on Preservative Fixation and Strength of CCA-Treated Lumber, R.S. Boone, J.E. Winandy, and J.J. Fuller, 9:65-73 (No. 8236).

Forest Resources and Wood Properties of Commerical Tree Species in the Russian Far East, O. Krankina and R.L. Ethington, 10:44-50 (No. 8247).

Impact of Log Sweep on Warp in Southern Pine Structural Lumber, F.G. Wagner and F.W. Taylor, 2:59-62 (No. 8218).

The Influence of Sawkerf and Target Size Reductions on Sawmill Revenue and Volume Recovery, T.C. Maness and Y. Lin, 11/12:43-50 (No. 8222).

Longitudinal and Radial Variation of Slope of Grain in Black Spruce Lumber, C. Tremblay, 1:79-83 (No. 8194).

A Mechanical Evaluation of Alaska White Spruce, D.E. Syta, K.C. Curtis, A.F. Gasbarro, and G.R. Sampson, 2:78-81 (No. 8168).

Mechanical Properties of Guatemalan Pine 2 by 4's, A. Rosales, G. Morales, and D. Green, 10:81-84 (No. 8203).

A New Method of Grading Lumber for Spiral Grain, I. Bindzi and M. Samson, 2:63-66 (No. 8190).

Perspectives on the Changing Economic Structure of the North American Softwood Lumber Industry, L.C. Irland, 6:53-60 (No. 8230).

Removing Fungal Stain From Ponderosa Pine by Caustic Bleaching, B.G. Lee, A. Maristany, C.C. Brunner, and J.J. Morrell, 3:56-60 (No. 8209).

Service Life of Posts from Alaska Tree Species Treated by Non-Pressure Methods, P. Mayer, G. Sampson, A. Gasbarro, and L. Allen, 11/12: 53-56 (No. 8051).

Shrinkage and Set in Drying of 4 by 4 Douglas-fir Lumber, Q. Wu and M.R. Milota, 5:59-63 (No. 8182).

TREATED WOOD PRODUCTS

Chemically Protecting Cellulosic String From Microbial Attack, J.J. Morrell and S.M. Smith, 6:84-89 (No. 8208).

Coupling Agent Improves Durability of PRF Bonds to CCA-Treated Southern Pine, C.B. Vick, 3:78-84 (No. 8181).

Decay and Soil Depletion Studies With Polymer/Boron Preservative Systems, R.J. Murphy, H.M. Barnes, and S.M. Gray, 9:77-81 (No. 8270).

Distribution of Chloropicrin in Douglas-fir Poles 1 to 7 Years After Remedial Treatment, P.F. Schneider, C.S. Love, and J.J. Morrell, 1:55-56 (No. 8196).

Effect of Selected Water-Soluble Bulking Chemicals on Moisture Diffusion and Dimensional Stability of Wood, Y. Chen, E.T. Choong, and H.M. Barnes, 5:84-90 (No. 8237).

Effect of Wood Moisture Content on Diffusion of Boron-Based Biocides Through Douglas-fir and Western Hemlock Lumber, J.J. Morrell and C.M. Freitag, 3:51-55 (No. 8213).

Effects of Redrying Schedule on Preservative Fixation and Strength of CCA-Treated Lumber, R.S. Boone, J.E. Winandy, and J.J. Fuller, 9:65-73 (No. 8236).

Efficacy of Chlorothalonil and Chlorothalonil Plus Chlorpyrifos Against Termite Attack, J.W. Creffield and N. Chew, 2:46-50 (No. 8205).

Evaluation of Diffusible Preservatives Using an Accelerated Field Simulator, B. Goodell, J. Liu, and J. Slahor, 6:74-76 (No. 8177).

Importation of Unprocessed Logs into North America: A Review of Pest Mitigation Procedures and Their Efficacy, J.J. Morrell, 9:41-50 (No. 8268).

Incidence of Decay Above the Groundline in Douglas-fir Poles in the Pacific Northwest, J.J. Morrell and P. Schneider, 5:80-83 (No. 8139).

Influence of Time-to-Failure on Strength of CCA-Treated Lumber, J.E. Winandy, 2:82-85 (No. 8157).

In Situ Bacterial Assay for Two Plywood Adhesives, R. Jagels, C.W. Murdoch, J. Pietroski, and J. Carlisle, 9:51-54 (No. 8274).

Laboratory Evaluation of the Decay Resistance of Red Oak (*Quercus rubra*) Pressure Treated with Copper Naphthenate, D.P. Kamdem, K. Gruber, and M. Freeman, 9:74-76 (No. 8269).

Modeling Data from Stake Tests of Waterborne Wood Preservatives, J.A. Cook and P.I. Morris, 11/12:61-65 (No. 8178).

Pacific Silver Fir is the More-Treatable Component of Hem-fir from Coastal British Columbia, P.I. Morris, 9:37-40 (No. 8289).

Performance and Durability of Finishes on Previously Coated CCA-Treated Wood, W.C. Feist and A.S. Ross, 9:29-36 (No. 8227).

Preliminary Development of Remedial Treatments for Thermally Degraded Fire-Retardant-Treated Wood, J.E. Winandy and E.L. Schmidt, 2:51-52 (No. 8195).

The Pressure Treatment of Wood With Sonic Waves, H.U. Nair and J. Simonsen, 9:59-64 (No. 8260).

Removing Fungal Stain From Ponderosa Pine by Caustic Bleaching, B.G. Lee, A. Maristany, C.C. Brunner, and J.J. Morrell, 3:56-60 (No. 8209).

A Review of Wood Crosstie Performance, S.S. Sonti, J.F. Davalos, M.G. Zipfel, and H.V.S. GangaRao, 9:55-58 (No. 8283).

Screening of Wood Preservatives: Comparison of the Soil-Block, Agar-Block, and Agar-Plate Tests, K. Archer, D.D. Nicholas, and T.P. Schultz, 1:86-89 (No. 8125).

Service Life of Posts from Alaska Tree Species Treated by Non-Pressure Methods, P. Mayer, G. Sampson, A. Gasbarro, and L. Allen, 11/12: 53-56 (No. 8051).

Wood Preservative Properties of Chlorpyrifos, P.E. Laks and M.S. Pruner, 2:67-71 (No. 8166).

COMPOSITES & MANUFACTURED PRODUCTS

FURNITURE & HARDWOOD VENEER/PLYWOOD

Fatigue Life and Design Stresses for Wood Composites Used in Furniture, Z. Bao and C.A. Eckelman, 7/8:59-63 (No. 8281).

Flattening Wavy Eucalyptus Veneer Through Pressure and Temperature: A Preliminary Laboratory Study, H.P. Steinhagen, V.F. Sagner, R.A. Ananias, and M.J. Poblete, 11/12:71-73 (No. 8187).

Information Sources Used by Furniture Retailers: The Importance of Furniture Markets, J.H. Michael and P.M. Smith, 4:25-30 (No. 8221).

Profile of the California Furniture Industry: Structure, Product Types, and Wood Use, D.H. Cohen and D. Goudie, 6:31-37 (No. 8216).

GLUING

Bending Strength of Spruce End-Grain Butt-Joints Using Resorcinol Formaldehyde-Based Adhesives, J-E. P. Nordström, 6:77-83 (No. 8210).

Coupling Agent Improves Durability of PRF Bonds to CCA-Treated Southern Pine, C.B. Vick, 3:78-84 (No. 8181).

Effect of Resin Type on Properties of Steam-Press-Cured Flakeboards, C-Y. Hse, R.L. Geimer, W.E. Hsu, and R.C. Tang, 1:57-62 (No. 8073).

In Situ Bacterial Assay for Two Plywood Adhesives, R. Jagels, C.W. Murdoch, J. Pietroski, and J. Carlisle, 9:51-54 (No. 8274).

In-Situ Cure Monitoring of Isocyanate Adhesives Using Microdielectric Analysis, M.P. Wolcott and T.G. Rials, 2: 72-77 (No. 8038).

Isocyanate Reactive Hot-Melt Adhesive for Veneer Laminates, E.D. Higgins, 10:72-76 (No. 8244).

Lignin-Modified Phenolic Adhesives for Bonding Radiata Pine Plywood, M. Olivares,

H. Aceituno, G. Neiman, E. Rivera, and T. Sellers, Jr., 1:63-67 (No. 8175).

HARDBOARD & INSULATION BOARD

Physical and Mechanical Properties of Hardboard Made of Black Locust Furnish, S. Hiziroglu and D.P. Kamdem, 11/12:66-70 (No. 8266).

Recycling Old Corrugated Containers as Furnish for Wet Process Hardboard, K.V. Kruse, 9:82-84 (No. 8275).

PULP & PAPER

Effect of Knife Clamp, Log Diameter, and Species on the Size Distribution of Pulp Chips Produced by a Chipper-Canter, R.E. Hernández and B. Quirion, 7/8:83-90 (No. 8184).

STRUCTURAL PANELS

Acetylated Rubberwood Flakeboard Resistance to Bio-Deterioration, Y.S. Hadi, I.G.K.T. Darma, F. Febrianto, and E.N. Herliyana, 10:64-66 (No. 8239).

Application of a Drill Resistance Technique for Density Profile Measurement in Wood Composite Panels, P.M. Winistorfer, W. Xu, and R. Wimmer, 6:90-93 (No. 8249).

Effect of Resin Type on Properties of Steam-Press-Cured Flakeboards, C-Y. Hse, R.L. Geimer, W.E. Hsu, and R.C. Tang, 1:57-62 (No. 8073).

Hygroscopic Deformation of Wood-Based Composite Panels, E.M. Lang, J.R. Loferski, and J.D. Dolan, 3:67-70 (No. 8173).

The Hygroscopic Warping of Laminated Panels, O. Suchsland, Y. Feng, and D. Xu, 10:57-63 (No. 8176).

Influence of Flake Characteristics on Horizontal Density Distribution of Flakeboard, P.R. Steiner and W. Xu, 4:61-66 (No. 8202).

In-Plane Hygroscopic Expansion of Plywood and Oriented Strandboard, E.M. Lang and J.R. Loferski, 4:67-71 (No. 8223).

Layer Thickness Swell and Layer Internal Bond of Medium Density Fiberboard and Oriented Strandboard, W. Xu and P.M. Winistorfer, 10:67-71 (No. 8250).

Lignin-Modified Phenolic Adhesives for Bonding Radiata Pine Plywood, M. Olivares, H. Aceituno, G. Neiman, E. Rivera, and T. Sellers, Jr., 1:63-67 (No. 8175).

Properties of Flakeboard Made From Northern White-Cedar, B.A. Haataja and P.E. Laks, 1:68-70 (No. 8174).

A Study of Formaldehyde and Other Organic Emissions From Pressing of Laboratory Oriented Strandboard, F.E. Carlson, E.K. Phillips, S.C. Tenhaeff, and W.D. Detlefsen, 3:71-77 (No. 8207).

WOOD ENGINEERING

FIRE PERFORMANCE & TECHNOLOGY

Preliminary Development of Remedial Treatments for Thermally Degraded Fire-Retardant-Treated Wood, J.E. Winandy and E.L. Schmidt, 2:51-52 (No. 8195).

LAMINATED WOOD COMPONENTS & ENGINEERED STRUCTURES

Increasing the Competitiveness of Structural Wood Composites Using Probabilistic Methods, D. Rosowsky and M.O. Hunt, 11/12:83-86 (No. 8259).

Performance of Glued-Laminated Timber Beams of European Manufacture, R. Falk and R. Hernández, 7/8:27-34 (No. 8282).

Red Maple and Yellow-Poplar LVL from Ultrasonically Rated Veneer, J.D. Kimmel and J.J. Janowiak, 7/8:54-58 (No. 8240).

Truss System for Developing Countries Using Small Diameter Roundwood and Dowel Nut Construction, C.A. Eckelman and J.F. Senft, 10:77-80 (No. 8300).

MECHANICAL FASTENING

The Influence of Wood Density on Metal-Plate Connector Mechanical Behavior Under Cyclic Loading, J.D. De Melo Moura, C. Bastian, G. Duchanois, J.M. Leban, and P. Triboulot, 11/12: 74-82 (No. 8299).

Practical Considerations of Dowel Bearing Strength and Annular Ring/Fastener Orientation, S.G. Winistorfer, 7/8:64-68 (No. 8279).

Simplified Models for the Properties of Dimension Lumber and Metal-Plate Connections at Elevated Temperatures, D. Shrestha, S. Cramer, and R. White, 7/8:35-42 (No. 8302).

WOOD ENGINEERING & MECHANICAL PROPERTIES

Application of a Drill Resistance Technique for Density Profile Measurement in Wood Composite Panels, P.M. Winistorfer, W. Xu, and R. Wimmer, 6:90-93 (No. 8249).

Directions for Duration-of-Load Research, D.V. Rosowsky and K.J. Fridley, 3:85-88 (No. 8193).

Effect of Imposed Load on Solid-Sawn Wood-Joist Floor Vibrations, J.D. Dolan, F.E. Woeste, and X. Li, 1:71-76 (No. 8124).

Fatigue Life and Design Stresses for Wood Composites Used in Furniture, Z. Bao and C.A. Eckelman, 7/8:59-63 (No. 8281).

Historical Perspective of Duration-of-Load Concepts, K.J. Fridley, M.O. Hunt, and J.F. Senft, 4:72-74 (No. 8197).

Increasing the Competitiveness of Structural Wood Composites Using Probabilistic Methods, D. Rosowsky and M.O. Hunt, 11/12:83-86 (No. 8259).

Influence of Time-to-Failure on Strength of CCA-Treated Lumber, J.E. Winandy, 2:82-85 (No. 8157).

The Influence of Wood Density on Metal-Plate Connector Mechanical Behavior Under Cyclic Loading, J.D. De Melo Moura, C. Bastian, G. Duchanois, J.M. Leban, and P. Triboulot, 11/12: 74-82 (No. 8299).

A Mechanical Evaluation of Alaska White Spruce, D.E. Syta, K.C. Curtis, A.F. Gasbarro, and G.R. Sampson, 2:78-81 (No. 8168).

Mechanical Properties of Guatemalan Pine 2 by 4's, A. Rosales, G. Morales, and D. Green, 10:81-84 (No. 8203).

Monte-Carlo Simulation Methods for Engineered Wood Systems, S.E. Taylor, M.H. Triche, D.A. Bender, and F.E. Woeste, 7/8:43-50 (No. 8130).

A New Method of Grading Lumber for Spiral Grain, I. Bindzi and M. Samson, 2:63-66 (No. 8190).

Physical and Mechanical Properties of Hardboard Made of Black Locust Furnish, S. Hiziroglu and D.P. Kamdem, 11/12:66-70 (No. 8266).

Practical Considerations of Dowel Bearing Strength and Annular Ring/Fastener Orientation, S.G. Winistorfer, 7/8:64-68 (No. 8279).

Red Maple and Yellow-Poplar LVL from Ultrasonically Rated Veneer, J.D. Kimmel and J.J. Janowiak, 7/8:54-58 (No. 8240).

Simplified Models for the Properties of Dimension Lumber and Metal-Plate Connections at Elevated Temperatures, D. Shrestha, S. Cramer, and R. White, 7/8:35-42 (No. 8302).

Stress Design of Wood Beam-Columns Using Exact Second-Order Moments, B. Kasal and T.H. Miller, 7/8:51-53 (No. 8171).

FUNDAMENTAL DISCIPLINES

BIOLOGY

Classification of Compression Wood Using Digital Image Analysis, C. Andersson and F. Walter, 11/12:87-92 (No. 8265).

Durability of Dahurian Larch, J.J. Morrell and C.M. Freitag, 1:77-78 (No. 8170).

Investigation for Brittleheart in Two *Eucalyptus Regnans* Logs, J.L. Yang and E.F. Dougal, 11/12:93-97 (No. 8277).

Longitudinal and Radial Variation of Slope of Grain in Black Spruce Lumber, C. Tremblay, 1:79-83 (No. 8194).

Screening of Wood Preservatives: Comparison of the Soil-Block, Agar-Block, and Agar-Plate Tests, K. Archer, D.D. Nicholas, and T.P. Schultz, 1:86-89 (No. 8125).

Wood Dust Concentrations for Three Hardwood Species and Moisture Contents, C.A. Lefevre, C.C. Hassler, and W.R. Myers, 2:53-58 (No. 8161).

CHEMISTRY

Acetylated Rubberwood Flakeboard Resistance to Bio-Deterioration, Y.S. Hadi, I.G.K.T. Darma, F. Febrianto, and E.N. Herliyana, 10:64-66 (No. 8239).

Investigation of Potential Toxicity and Mutagenicity of Distillates From the Drying of Five Species of Wood, J.T. Singer, J.A. Jackson, and R.W. Rice, 5:45-50 (No. 8238).

Removing Fungal Stain From Ponderosa Pine by Caustic Bleaching, B.G. Lee, A. Maristany, C.C. Brunner, and J.J. Morrell, 3:56-60 (No. 8209).

A Study of Formaldehyde and Other Organic Emissions From Pressing of Laboratory Oriented Strandboard, F.E. Carlson, E.K. Phillips, S.C. Tenhaeff, and W.D. Detlefsen, 3:71-77 (No. 8207).

PHYSICS

Bulk Density of Bottomland Hardwoods in East Texas and West Louisiana, J.D. Lenhart, J.T. Lee, and H.A. Londo, 10:85-88 (No. 8096).

Classification of Compression Wood Using Digital Image Analysis, C. Andersson and F. Walter, 11/12:87-92 (No. 8265).

Development of a Rapid Wood Density Evaluation Instrument, E.A. Hamm, 4:75-82 (No. 7968).

Differences in Moisture Content and Shrinkage Between Innerwood and Outerwood of a Single Cottonwood Tree, T.F. Shupe, E.T. Choong, and M.D. Gibson, 10:89-92 (No. 8294).

Differences in Moisture Content and Shrinkage Between Outerwood, Middlewood, and Corewood of Two Yellow-Poplar Trees, T.F. Shupe, E.T. Choong, and M.D. Gibson, 9:85-90 (No. 8256).

Effect of Selected Water-Soluble Bulking Chemicals on Moisture Diffusion and Dimensional Stability of Wood, Y. Chen, E.T. Choong, and H.M. Barnes, 5:84-90 (No. 8237).

Higher Heating Values for Pellets Made From Woodwaste and Recycled Newsprint, R.W. Rice and R.M. Willey, 1:84-85 (No. 8179).

Hygroscopic Deformation of Wood-Based Composite Panels, E.M. Lang, J.R. Loferski, and J.D. Dolan, 3:67-70 (No. 8173).

The Hygroscopic Warping of Laminated Panels, O. Suchsland, Y. Feng, and D. Xu, 10:57-63 (No. 8176).

Improving Visual Color Sorting of Dimension Stock, A.D. Pugel, J.E. Phelps, and D.D. Stokke, 11/12:57-60 (No. 8267).

In-Plane Hygroscopic Expansion of Plywood and Oriented Strandboard, E.M. Lang and J.R. Loferski, 4:67-71 (No. 8223).

Layer Thickness Swell and Layer Internal Bond of Medium Density Fiberboard and Oriented Strandboard, W. Xu and P.M. Winistorfer, 10:67-71 (No. 8250).

Transport Coefficients for Six Log and Lumber End Coatings, R.W. Rice, 5:64-68 (No. 8188).

Variation in Lightness of White Oak Dimension Stock, D.D. Stokke, A.D. Pugel, and J.E. Phelps, 10:51-56 (No. 8199).

Variation of Final Moisture Content of 4/4 Yellow-Poplar Lumber Dried in a Small Dehumidification Kiln, J.P. Armstrong and D.W. Patterson, 5:51-52 (No. 8290).

FEATURE ARTICLES

The Crisis in Wood Science and Technology Education, D.E. Lyon, F.C. Beall, and W.L. Galligan, 6:23-28 (No. 8365).

Engineered Wood Products: The Future is Bright, L.M. Guss, 7/8:17-24 (No. 8387).

Lumber Drying: Today and Tomorrow, G. Wengert and J. Denig, 5:22-30 (No. 8342).

Resiliency: The Trademark of American Forests, D. MacCleery, 1:18-28 (No. 8295).

Unlikely Partners? The Marriage of Wood and Nonwood Materials, J.A. Youngquist, 10:25-30 (No. 8411).

U.S. Forests and Forest Products: Fact vs. Perception, J. Bowyer, 11/12:17-24 (No. 8412).

Wood Adhesives and Binders: What's the Outlook?, J.T. White, 3:21-28 (No. 8334).

Wood and Other Raw Materials for the 21st Century: Where Will They Come From? J. Bowyer, 2:17-24 (No. 8296).

Wood Preservation: The Classics and the New Age, H.M. Barnes and R.J. Murphy, 9:17-26 (No. 8412).

A

Aceituno, H., see Olivares, M.

Allen, L., see Mayer, P.

Ananias, R.A., see Steinhagen, H.P.

Andersson, C. and F. Walter, Classification of Compression Wood Using Digital Image Analysis, 11/12:87-92 (No. 8265).

Araman, P.A., see Harris, R.A.

Araman, P.A., see Lin, W.

Araman, P.A., see Wiedenbeck, J.K.

Archer, K., D.D. Nicholas, and T.P. Schultz, Screening of Wood Preservatives: Comparison of the Soil-Block, Agar-Block, and Agar-Plate Tests, 1:86-89 (No. 8125).

Armstrong, J.P. and D.W. Patterson, Variation of Final Moisture Content of 4/4 Yellow-Poplar Lumber Dried in a Small Dehumidification Kiln, 5:51-52 (No. 8290).

Atanackovic, A., see Lavery, D.J.

B

Bao, Z. and C.A. Eckelman, Fatigue Life and Design Stresses for Wood Composites Used in Furniture, 7/8:59-63 (No. 8281).

Barnes, H.M. and R.J. Murphy, Wood Preservation: The Classics and the New Age, 9:17-26 (No. 8412).

Barnes, H.M., see Chen, Y.

Barnes, H.M., see Murphy, R.J.

Bastian, C., see De Melo Moura, J.D.

Beall, F.C., see Lyon, D.E.

Bender, D.A., see Taylor, S.E.

Bialozynski, L., see Briggs, D.

Bindzi, I. and M. Samson, A New Method of Grading Lumber for Spiral Grain, 2:63-66 (No. 8190).

Boone, R.S., J.E. Winandy, and J.J. Fuller, Effects of Redrying Schedule on Preservative Fixation and Strength of CCA-Treated Lumber, 9:65-73 (No. 8236).

Bowyer, J., U.S. Forests and Forest Products: Fact vs. Perception, 11/12:17-24 (No. 8412).

Bowyer, J., Wood and Other Raw Materials for the 21st Century: Where Will They Come From?, 2:17-24 (No. 8296).

Bratkovich, S.M., see Gephart, J.S.

Briggs, D. and L. Bialozynski, Use of Wood Raw Materials by the U.S. Millwork Industry in 1990, 2:27-34 (No. 8158).

Broman, N.O., Visual Impressions of Features in Scots Pine Wood Surfaces: A Qualitative Study, 3:61-66 (No. 8146).

Brunner, C.C., see Lee, B.G.

Bush, R.J., see Punches, J.W.

C

Carino, H.F., W. Lin, K. Muehlenfeld, J. Gober, and P. Waldrop, Wood Products Mill Improvement: An Important Component of Rural Development, 6:47-52 (No. 8234).

Carino, H.F., W. Lin, K. Muehlenfeld, and Y. Li, Systems Approach to Equipment Replacement in Wood Products Manufacturing, 6:61-68 (No. 8245).

Carlisle, J., see Jagels, R.

Carlson, F.E., E.K. Phillips, S.C. Tenhaeff, and W.D. Detlefsen, A Study of Formaldehyde and Other Organic Emissions From Pressing of Laboratory Oriented Strandboard, 3:71-77 (No. 8207).

Chase,W.E., see Howard, T.E.

Chen, Y., E.T. Choong, and H.M. Barnes, Effect of Selected Water-Soluble Bulking Chemicals on Moisture Diffusion and Dimensional Stability of Wood, 5:84-90 (No. 8237).

Chew, N., see Creffield, J.W.

Choong, E.T., see Chen, Y.

Choong, E.T., see Shupe, T.F.

Cohen, D.H. and D. Goudie, Profile of the California Furniture Industry: Structure, Product Types, and Wood Use, 6:31-37 (No. 8216).

Cook, J.A. and P.I. Morris, Modeling Data from Stake Tests of Waterborne Wood Preservatives, 11/12:61-65 (No. 8178).

Cramer, S., see Shrestha, D.

Creffield, J.W. and N. Chew, Efficacy of Chlorothalonil and Chlorothalonil Plus Chlorpyrifos Against Termite Attack, 2:46-50 (No. 8205).

Cubbage, F.W., see Wagner, J.E.

Curtis, K.C., see Syta, D.E.

D

Darma, I.G.K.T., see Hadi, Y.S.

Davalos, J.F., see Sonti, S.S.

De Melo Moura, J.D., C. Bastian, G. Duchanois, J.M. Leban, and P. Triboulot, The Influence of Wood Density on Metal-Plate Connector Mechanical Behavior Under Cyclic Loading, 11/12:74-82 (No. 8299).

Denig, J., see Wengert, G.

Detlefsen, W.D., see Carlson, F.E.

Dolan, J.D., F.E. Woeste, and X. Li, Effect of Imposed Load on Solid-Sawn Wood-Joist Floor Vibrations, 1:71-76 (No. 8124).

Dolan, J.D., see Lang, E.M.

Dougal, E.F., see Yang, J.L.

Dramm, J.R., see Fuller, J.J.

Dramm, J.R., see Ross, R.J.

Duchanois, G., see De Melo Moura, J.D.

E

Eckelman, C.A. and J.F. Senft, Truss System for Developing Countries Using Small Diameter Roundwood and Dowel Nut Construction, 10:77-80 (No. 8300).

Eckelman, C.A., see Bao, Z.

Elowsson, T. and K. Liukko, How to Achieve Effective Wet Storage of Pine Logs (*Pinus sylvestris*) With a Minimum Amount of Water, 11/12:36-42 (No. 8246).

Ethington, R.L., see Krankina, O.

F

Falk, R. and R. Hernández, Performance of Glued-Laminated Timber Beams of European Manufacture, 7/8:27-34 (No. 8282).

Febrianto, F., see Hadi, Y.S.

Feist, W.C. and A.S. Ross, Performance and Durability of Finishes on Previously Coated CCA-Treated Wood, 9:29-36 (No. 8227).

Feist, W.C., see Richter, K.

Feng, Y., see Suchsland, O.

Fiedler, C.E., see Keegan, C.E., III

Freeman, M., see Kamdem, D.P.

Freitag, C.M., see Morrell, J.J.

Fridley, K.J., M.O. Hunt, and J.F. Senft, Historical Perspective of Duration-of-Load Concepts, 4:72-74 (No. 8197).

Fridley, K.J., see Rosowsky, D.V.

Fuller, J.J., R.J. Ross, and J.R. Dramm, Nondestructive Evaluation of Honeycomb and Surface Checks in Red Oak Lumber, 5:42-44 (No. 8324).

Fuller, J.J., see Boone, R.S.

Fuller, J.J., see Ross, R.J.

G

Galligan, W.L., see Lyon, D.E.

GangaRao, H.V.S., see Sonti, S.S.

Gasbarro, A., see Mayer, P.

Gasbarro, A.F., see Syta, D.E.

Gatchell, C.J., J.K. Wiedenbeck, and E.S. Walker, Understanding That Red Oak Lumber Has a Better and Worse End, 4:54-60 (No. 8229).

Gatchell, C.J., see Wiedenbeck, J.K.

Gazo, R. and P.H. Steele, Rough Mill Analysis Model, 4:51-53 (No. 8189).

Gazo, R., see Steele, P.H.

Geimer, R.L., see Hse, C-Y.

Gephart, J.S., H.D. Petersen, and S.M. Bratkovich, Green Dimensioning: A Review of Processing, Handling, Drying, and Marketing, 5:69-73 (No. 8257).

Gibson, M.D., see Shupe, T.F.

Gober, J., see Carino, H.F.

Goodell, B., J. Liu, and J. Slahor, Evaluation of Diffusible Preservatives Using an Accelerated Field Simulator, 6:74-76 (No. 8177).

Goudie, D., see Cohen, D.H.

Gough, D.K., see McNaught, A.M.

Gray, S.M., see Murphy, R.J.

Green, D., see Rosales, A.

Gruber, K., see Kamdem, D.P.

Guss, L.M., Engineered Wood Products: The Future is Bright, 7/8:17-24 (No. 8387).

H

Haas, M.P., see Smith, P.M.

Haataja, B.A. and P.E. Laks, Properties of Flakeboard Made From Northern White-Cedar, 1:68-70 (No. 8174).

Hadi, Y.S., I.G.K.T. Darma, F. Febrianto, and E.N. Herliyana, Acetylated Rubberwood Flakeboard Resistance to Bio-Deterioration, 10:64-66 (No. 8239).

Hamm, E.A., Development of a Rapid Wood Density Evaluation Instrument, 4:75-82 (No. 7968).

Hansen, B.G., Estimating the Tropical/Temperate Mix of European Hardwood Lumber Imports, 1:37-39 (No. 8116).

Hansen, E.N., see Punches, J.W.

Harris, R.A. and P.A. Araman, The Correlation Between Green Density and the Occurrence of Honeycomb in Kiln-Dried Red Oak Lumber, 5:53-54 (No. 7940).

Hassler, C.C., see Lefevre, C.A.

Herliyana, E.N., see Hadi, Y.S.

Hernández, R.E. and B. Quirion, Effect of Knife Clamp, Log Diameter, and Species on the Size Distribution of Pulp Chips Produced by a Chipper-Canter, 7/8:83-90 (No. 8184).

Hernández, R., see Falk, R.

Higgins, E.D., Isocyanate Reactive Hot-Melt Adhesive for Veneer Laminates, 10:72-76 (No. 8244).

Hiziroglu, S. and D.P. Kamdem, Physical and Mechanical Properties of Hardboard Made of Black Locust Furnish,11/12:66-70 (No. 8266).

Howard, T.E. and W.E. Chase, Maine Stumpage Prices: Characteristics and Trends from 1963 to 1990, 1:31-36 (No. 8123).

Hse, C-Y., R.L. Geimer, W.E. Hsu, and R.C. Tang, Effect of Resin Type on Properties of Steam-Press-Cured Flakeboards, 1:57-62 (No. 8073).

Hsu, W.E., see Hse, C-Y.

Hunt, M.O., see Fridley, K.J.

Hunt, M.O., see Rosowsky, D.

Hutton, S.G., see Taylor, J.

I

Irland, L.C., Perspectives on the Changing Economic Structure of the North American Softwood Lumber Industry, 6:53-60 (No. 8230).

J

Jackson, J.A., see Singer, J.T.

Jagels, R., C.W. Murdoch, J. Pietroski, and J. Carlisle, *In Situ* Bacterial Assay for Two Plywood Adhesives, 9:51-54 (No. 8274).

Janowiak, J.J., see Kimmel, J.D.

K

Kamdem, D.P., K. Gruber, and M. Freeman, Laboratory Evaluation of the Decay Resistance of Red Oak (*Quercus rubra*) Pressure Treated with Copper Naphthenate, 9:74-76 (No. 8269).

Kamdem, D.P., see Hiziroglu, S.

Kasal, B. and T.H. Miller, Stress Design of Wood Beam-Columns Using Exact Second-Order Moments, 7/8:51-53 (No. 8171).

Keegan, C.E., III, C.E. Fiedler, and D.P. Wichman, Costs Associated with Harvest Activities for Major Harvest Systems in Montana, 7/8:78-82 (No. 8242).

Kimmel, J.D. and J.J. Janowiak, Red Maple and Yellow-Poplar LVL from Ultrasonically Rated Veneer, 7/8:54-58 (No. 8240).

Kline, D.E., see Lin, W.

Knaebe, M.T., see Richter, K.

Krankina O. and R.L. Ethington, Forest Resources and Wood Properties of Commerical Tree Species in the Russian Far East, 10:44-50 (No. 8247).

Kruse, K.V., Recycling Old Corrugated Containers as Furnish for Wet Process Hardboard, 9:82-84 (No. 8275).

L

Laks, P.E. and M.S. Pruner, Wood Preservative Properties of Chlorpyrifos, 2:67-71 (No. 8166).

Laks, P.E., see Haataja, B.A.

Lanford, B.L. and B.J. Stokes, Comparison of Two Thinning Systems. Part 1. Stand and Site Impacts, 5:74-79 (No. 8228).

Lang, E.M. and J.R. Loferski, In-Plane Hygroscopic Expansion of Plywood and Oriented Strandboard, 4:67-71 (No. 8223).

Lang, E.M., J.R. Loferski, and J.D. Dolan, Hygroscopic Deformation of Wood-Based Composite Panels, 3:67-70 (No. 8173).

Lavery, D.J., D. McLarnon, J.M. Taylor, S. Moloney, and A. Atanackovic, Parameters Affecting the Surface Finish of Planed Sitka Spruce, 4:45-50 (No. 8201).

Leban, J., see De Melo Moura, J.D.

Lee, B.G., A. Maristany, C.C. Brunner, and J.J. Morrell, Removing Fungal Stain From Ponderosa Pine by Caustic Bleaching, 3:56-60 (No. 8209).

Lee, J.T., see Lenhart, J.D.

Lefevre, C.A., C.C. Hassler, and W.R. Myers, Wood Dust Concentrations for Three Hardwood Species and Moisture Contents, 2:53-58 (No. 8161).

Lenhart, J.D., J.T. Lee, and H.A. Londo, Bulk Density of Bottomland Hardwoods in East Texas and West Louisiana, 10:85-88 (No. 8096).

Li, Y., see Carino, H.F.

Li, X., see Dolan, J.D.

Lin, W., D.E. Kline, P.A. Araman, and J.K. Wiedenbeck, Design and Evaluation of Log-to-Dimension Manufacturing Systems Using System Simulation, 3:37-44 (No. 8217).

Lin, W., D.E. Kline, P.A. Araman, and J.K. Wiedenbeck, Producing Hardwood Dimension Parts Directly From Logs: An Economic Feasibility Study, 6:38-46 (No. 8248).

Lin, W., see Carino, H.F.

Lin, Y., see Maness, T.C.

Little, R.L. and W.W. Moschler, Controlling Corrosion in Lumber Dry Kiln Buildings, 5:55-58 (No. 8258).

Liu, J., see Goodell, B.

Liukko, K., see Elowsson, T.

Loferski, J.R., see Lang, E.M.

Londo, H.A., see Lenhart, J.D.

Love, C.S., see Schneider, P.F.

Luppold, W.G., Regional Differences in the Eastern Hardwood Sawmilling Industry, 10:39-43 (No. 8263).

Luppold, W.G., see Smith, P.M.

Lyon, D.E., F.C. Beall, and W.L. Galligan, The Crisis in Wood Science and Technology Education, 6:23-28 (No. 8365).

M

MacCleery, D., Resiliency: The Trademark of American Forests, 1:18-28 (No. 8295).

Maness, T.C. and Y. Lin, The Influence of Sawkerf and Target Size Reductions on Sawmill Revenue and Volume Recovery, 11/12:43-50 (No. 8222).

Maristany, A., see Lee, B.G.

Mayer, P., G. Sampson, A. Gasbarro, and L. Allen, Service Life of Posts from Alaska Tree Species Treated by Non-Pressure Methods, 11/12:53-56 (No. 8051).

McLarnon, D., see Lavery, D.J.

McNaught, A.M. and D.K. Gough, Drying 40-mm-Thick Slash Pine in 2.5 Hours at 200°C, 1:51-54 (No. 7965).

Michael, J.H. and P.M. Smith, Information Sources Used by Furniture Retailers: The Importance of Furniture Markets, 4:25-30 (No. 8221).

Michael, J.H., see Mulhern, F.J.

Miller, T.H., see Kasal, B.

Milota, M.R. and E.M. Wengert, Applied Drying Technology, 1988 to 1993, 5:33-42 (No. 8285).

Milota, M.R., see Wu, Q.

Moloney, S., see Lavery, D.J.

Morales, G., see Rosales, A.

Morrell, J.J., Importation of Unprocessed Logs into North America: A Review of Pest Mitigation Procedures and Their Efficacy, 9:41-50 (No. 8268).

Morrell, J.J. and C.M. Freitag, Durability of Dahurian Larch, 1:77-78 (No. 8170).

Morrell, J.J. and C.M. Freitag, Effect of Wood Moisture Content on Diffusion of Boron-Based Biocides Through Douglas-fir and Western Hemlock Lumber, 3:51-55 (No. 8213).

Morrell, J.J. and P. Schneider, Incidence of Decay Above the Groundline in Douglas-fir Poles in the Pacific Northwest, 5:80-83 (No. 8139).

Morrell, J.J. and S.M. Smith, Chemically Protecting Cellulosic String From Microbial Attack, 6:84-89 (No. 8208).

Morrell, J.J., see Lee, B.G.

Morrell, J.J., see Schneider, P.F.

Morris, P.I., Pacific Silver Fir is the More-Treatable Component of Hem-fir from Coastal British Columbia, 9:37-40 (No. 8289).

Morris, P.I., see Cook, J.A.

Moschler, W.W., see Little, R.L.

Muehlenfeld, K., see Carino, H.F.

Mulhern, F.J. and J.H. Michael, The Effect of Retail Promotions on Homecenter Shopping Behavior, 3:31-36 (No. 8172).

Murdoch, C.W., see Jagels, R.

Murphy, R.J., H.M. Barnes, and S.M. Gray, Decay and Soil Depletion Studies With Polymer/Boron Preservative Systems, 9:77-81 (No. 8270).

Murphy, R.J., see Barnes, H.M.

Myers, W.R., see Lefevre, C.A.

N

Nair, H.U. and J. Simonsen, The Pressure Treatment of Wood With Sonic Waves, 9:59-64 (No. 8260).

Nicholas, D.D., see Archer, K.

Niemela, J.S. and P.M. Smith, A Marketing Strategy Comparison: Finland, Western United States, and British Columbia, 11/12: 27-35 (No. 8286).

Neiman, G., see Olivares, M.

Nordström, J-E. P., Bending Strength of Spruce End-Grain Butt-Joints Using Resorcinol Formaldeyde-Based Adhesives, 6:77-83 (No. 8210).

O

Olivares, M., H. Aceituno, G. Neiman, E. Rivera, and T. Sellers, Jr., Lignin-Modified Phenolic Adhesives for Bonding Radiata Pine Plywood, 1:63-67 (No. 8175).

P

Patterson, D.W., see Armstrong, J.P.

Petersen, H.D., see Gephart, J.S.

Phelps, J.E., see Pugel, A.D.

Phelps, J.E., see Stokke, D.D.

Phillips, E.K., see Carlson, F.E.

Pietroski, J., see Jagels, R.

Poblete, M.J., see Steinhagen, H.P.

Pruner, M.S., see Laks, P.E.

Pugel, A.D., J.E. Phelps, and D.D. Stokke, Improving Visual Color Sorting of Dimension Stock, 11/12:57-60 (No. 8267).

Pugel, A.D., see Stokke, D.D.

Punches, J.W., E.N. Hansen, and R.J. Bush, Productivity Characteristics of the U.S. Wood Cabinet Industry,10:33-38 (No. 8253).

Q

Quirion, B., see Hernández, R.E.

R

Redmond, C.H., see Wagner, J.E.

Rials, T.G., see Wolcott, M.P.

Rice, R.W., Transport Coefficients for Six Log and Lumber End Coatings, 5:64-68 (No. 8188).

Rice, R.W. and R.M. Willey, Higher Heating Values for Pellets Made From Woodwaste and Recycled Newsprint, 1:84-85 (No. 8179).

Rice, R.W., see Singer, J.T.

Richter, K., W.C. Feist, and M.T. Knaebe, The Effect of Surface Roughness on the Performance of Finishes. Part 1. Roughness Characterization and Stain Performance, 7/8:91-97 (No. 8254).

Rivera, E., see Olivares, M.

Rosales, A., G. Morales, and D. Green, Mechanical Properties of Guatemalan Pine 2 by 4's, 10:81-84 (No. 8203).

Rosowsky, D.V., and K.J. Fridley, Directions for Duration-of-Load Research, 3:85-88 (No. 8193).

Rosowsky, D. and M.O. Hunt, Increasing the Competitiveness of Structural Wood Composites Using Probabilistic Methods, 11/12:83-86 (No. 8259).

Ross, A.S., see Feist, W.C.

Ross, R.J., J.J. Fuller, and J.R. Dramm, Nondestructive Evaluation of Green Defect-Prone Red Oak Lumber: A Pilot Study, 11/12:51-52 (No. 8316).

Ross, R.J., see Fuller, J.J.

S

Sagner, V.F., see Steinhagen, H.P.

Sampson, G.R., see Syta, D.E.

Sampson, G., see Mayer, P.

Samson, M., see Bindzi, I.

Saucier, J.R., see Syme, J.H.

Schmidt, E.L., see Winandy, J.E.

Schneider, P.F., C.S. Love, and J.J. Morrell, Distribution of Chloropicrin in Douglas-fir Poles 1 to 7 Years After Remedial Treatment, 1:55-56 (No. 8196).

Schneider, P., see Morrell, J.J.

Schultz, T.P., see Archer, K.

Sellers, T., Jr., see Olivares, M.

Senft, J.F., see Eckelman, C.A.

Senft, J.F., see Fridley, K.J.

Shrestha, D., S. Cramer, and R. White, Simplified Models for the Properties of Dimension Lumber and Metal-Plate Connections at Elevated Temperatures, 7/8:35-42 (No. 8302).

Shupe, T.F., E.T. Choong, and M.D. Gibson, Differences in Moisture Content and Shrinkage Between Innerwood and Outerwood of a Single Cottonwood Tree, 10:89-92 (No. 8294).

Shupe, T.F., E.T. Choong, and M.D. Gibson, Differences in Moisture Content and Shrinkage Between Outerwood, Middlewood, and Corewood of Two Yellow-Poplar Trees, 9:85-90 (No. 8256).

Simonsen, J., see Nair, H.U.

Singer, J.T., J.A. Jackson, and R.W. Rice, Investigation of Potential Toxicity and Mutagenicity of Distillates From the Drying of Five Species of Wood, 5:45-50 (No. 8238).

Slahor, J., see Goodell, B.

Smith, P.M., M.P. Haas, and W.G. Luppold, An Analysis of Tropical Hardwood Product Importation and Consumption in the United States, 4:31-38 (No. 8165).

Smith, P.M., see Michael, J.H.

Smith, P.M., see Niemela, J.S.

Smith, P.M., see Vlosky, R.P.

Smith, S.M., see Morrell, J.J.

Sonti, S.S., J.F. Davalos, M.G. Zipfel, and H.V.S. GangaRao, A Review of Wood Crosstie Performance, 9:55-58 (No. 8283).

Steele, P.H. and R. Gazo, A Procedure for Determining the Benefits of Sorting Lumber By Grade Prior to Rough Mill Processing, 6:69-73 (No. 8191).

Steele, P.H., see Gazo, R.

Steiner, P.R. and W. Xu, Influence of Flake Characteristics on Horizontal Density Distribution of Flakeboard, 4:61-66 (No. 8202).

Steinhagen, H.P., V.F. Sagner, R.A. Ananias, and M.J. Poblete, Flattening Wavy Eucalyptus Veneer Through Pressure and Temperature: A Preliminary Laboratory Study, 11/12:71-73 (No. 8187).

Stokes, B.J., see Lanford, B.L.

Stokke, D.D., A.D. Pugel, and J.E. Phelps, Variation in Lightness of White Oak Dimension Stock, 10:51-56 (No. 8199).

Stokke, D.D., see Pugel, A.D.

Suchsland, O., Y. Feng, and D. Xu, The Hygroscopic Warping of Laminated Panels, 10:57-63 (No. 8176).

Syme, J.H. and J.R. Saucier, Effects of Long-Term Storage of Southern Pine Sawlogs Under Water Sprinklers, 1:47-50 (No. 8186).

Syta, D.E., K.C. Curtis, A.F. Gasbarro, and G.R. Sampson, A Mechanical Evaluation of Alaska White Spruce, 2:78-81 (No. 8168).

T

Tang, R.C., see Hse, C-Y.

Taylor, F.W., see Wagner, F.G.

Taylor, J. and S.G. Hutton, Simplified Band-saw Tensioning Procedure to Improve Blade Stiffness and Cutting Accuracy, 4:38-44 (No. 8117).

Taylor, J.M., see Lavery, D.J.

Taylor, S.E., M.H. Triche, D.A. Bender, and F.E. Woeste, Monte-Carlo Simulation Methods for Engineered Wood Systems, 7/8:43-50 (No. 8130).

Tenhaeff, S.C., see Carlson, F.E.

Tremblay, C., Longitudinal and Radial Variation of Slope of Grain in Black Spruce Lumber, 1:79-83 (No. 8194).

Triboulot, P., see De Melo Moura, J.D.

Triche, M.H., see Taylor, S.E.

V

Vick, C.B., Coupling Agent Improves Durability of PRF Bonds to CCA-Treated Southern Pine, 3:78-84 (No. 8181).

Vlosky, R.P. and P.M. Smith, UPC Barcoding for Homecenter Retail Customers: The Wood Products Supplier Perspective, 2:35-40 (No. 8198).

W

Wagner, F.G. and F.W. Taylor, Impact of Log Sweep on Warp in Southern Pine Structural Lumber, 2:59-62 (No. 8218).

Wagner, J.E., F.W. Cubbage, and C.H. Redmond, Comparing the Capital Asset Pricing Model and Capital Budgeting Techniques to Analyze Timber Investments, 7/8:69-77 (No. 8121).

Waldrop, P., see Carino, H.F.

Walker, E.S., see Gatchell, C.J.

Walker, E.S., see Wiedenbeck, J.K.

Walter, F., see Andersson, C.

Wengert, E.M., see Milota, M.R.

Wengert, G. and J. Denig, Lumber Drying: Today and Tomorrow, 5:22-30 (No. 8342).

White, J.T., Wood Adhesives and Binders: What's the Outlook?, 3:21-28 (No. 8334).

White, R., see Shrestha, D.

Wichman, D.P., see Keegan, C.E., III

Wiedenbeck, J.K. and P.A. Araman, Rough Mill Simulations Reveal That Productivity When Processing Short Lumber Can Be High, 1:40-46 (No. 8185).

Wiedenbeck, J.K., C.J. Gatchell, and E.S. Walker, Quality Characteristics of Appalachian Red Oak Lumber, 3:45-50 (No. 8200).

Wiedenbeck, J.K., see Gatchell, C.J.

Wiedenbeck, J.K., see Lin, W.

Willey, R.M., see Rice, R.W.

Wimmer, R., see Winistorfer, P.M.

Winandy, J.E., Influence of Time-to-Failure on Strength of CCA-Treated Lumber, 2:82-85 (No. 8157).

Winandy, J.E. and E.L. Schmidt, Preliminary Development of Remedial Treatments for Thermally Degraded Fire-Retardant-Treated Wood, 2:51-52 (No. 8195).

Winandy, J.E., see Boone, R.S.

Winistorfer, P.M., W. Xu, and R. Wimmer, Application of a Drill Resistance Technique for Density Profile Measurement in Wood Composite Panels, 6:90-93 (No. 8249).

Winistorfer, P.M., see Xu, W.

Winistorfer, S.G., Practical Considerations of Dowel Bearing Strength and Annular Ring/Fastener Orientation, 7/8:64-68 (No. 8279).

Woeste, F.E., see Dolan, J.D.

Woeste, F.E., see Taylor, S.E.

Wolcott, M.P. and T.G. Rials, In-Situ Cure Monitoring of Isocyanate Adhesives Using Microdielectric Analysis, 2:72-77 (No. 8038).

Wu, Q. and M.R. Milota, Shrinkage and Set in Drying of 4 by 4 Douglas-fir Lumber, 5:59-63 (No. 8182).

X

Xu, D., see Suchsland, O.

Xu, W. and P.M. Winistorfer, Layer Thickness Swell and Layer Internal Bond of Medium Density Fiberboard and Oriented Strandboard, 10:67-71 (No. 8250).

Xu, W., see Steiner, P.R.

Xu, W., see Winistorfer, P.M.

Y

Yang, J.L. and E.F. Dougal, Investigation for Brittleheart in Two *Eucalyptus Regnans* Logs, 11/12:93-97 (No. 8277).

Youngquist, J.A., Unlikely Partners? The Marriage of Wood and Nonwood Materials, 10:25-30 (No. 8411).

Z

Zavala, D.Z., The Effect of Log Length and Lumber Thickness Over-Allowance on Lumber Recovery, 2:41-45 (No. 8140).

Zipfel, M.G., see Sonti, S.S.